


| Nominal diameter | | I.D. | O.D. | Weight (reference) | L/coil | Allowable pressure (at room temperature) Bar (MPa) | Allowable bending radius mm |
|------------------|------|-------|-------|--------------------|--------|---|--------------------------------|
| mm | inch | mm | mm | g/m | m | | |
| * 32 | 1¼ | 32.0 | 41.8 | 765 | | | 300 |
| 38 | 1½ | 38.0 | 48.5 | 910 | | | 350 |
| 50 | 2 | 50.8 | 61.4 | 1230 | | 4 (0.40) | 550 |
| 65 | 2½ | 63.5 | 76.0 | 1805 | 20-50 | | 800 |
| 75 | 3 | 76.2 | 89.5 | 2200 | | | 850 |
| 90 | 3½ | 88.9 | 102.0 | 2510 | | 3 (0.30) | 1110 |
| 100 | 4 | 101.6 | 117.0 | 3340 | | | 1250 |
| 125 | 5 | 127.3 | 142.0 | 4060 | 20 | 2.5 (0.25) | 2250 |
| 150 | 6 | 152.4 | 169.4 | 5730 | | 2 (0.20) | 2750 |
| 200 | 8 | 203.2 | 226.4 | 9960 | 10 | | 4000 |

CSIZES MARKED * WILL BE BUILT-TO-ORDER PRODUCTS

ขนาดที่มีเครื่องหมาย * เป็นผลิตภัณฑ์ที่ผลิตตามคำสั่งซื้อ

| Material | Abrasion mass (g) | | Abrasion volume (cm ³) | |
|---|-------------------|----|------------------------------------|---|
| | Ratio | | Ratio | |
| Special polyurethane resin of abrasion resistance | 0.232 | 1 | 0.219 | 1 |
| SGP | 13.811 | 60 | 1.759 | 8 |
| SUS304 TP | 10.083 | 43 | 1.271 | 6 |

STRAUB COUPLING



| Nominal diameter | | Connection of Hose to Hose | Connection of Hose to Pipe | D | W |
|------------------|------|----------------------------|----------------------------|-------|-------|
| mm | inch | Part No. | Part No. | mm | mm |
| 50 | 2 | FX-64E | FXT-64E | 86.0 | 76.4 |
| 65 | 2½ | FX-77E | FXT-77E | 106.0 | |
| 75 | 3 | FX-90E | | 119.0 | 95.0 |
| 100 | 4 | FX-117E | | 146.0 | |
| 125 | 5 | FX-143E | FXT-143E | 174.0 | |
| 150 | 6 | FX-171E | FXT-171E | 200.0 | 110.0 |
| 200 | 8 | FX-226E | FXT-226E | 262.0 | 141.0 |

CAUTIONS / ข้อควรระวัง

- NOT SUITABLE FOR THE FLUID WHICH CONTAIN OIL.
- ไม่เหมาะสำหรับของเหลวที่มีส่วนผสมของน้ำมัน